

# DTElabs

## DTL-100 Desktop Tally Light

## Specifications

### Key Features

- Talent and Operator Tally light
- External tally trigger for monitors with supported tally input
- Talent tally on/off switch
- 1/4 20 mounting
- All metal construction
- Powers direct from main Interface no external power needed
- Extends greater than to 800 meters
- Main transmitter units TI-800 & TPI-400



External Tally	
01	LED
02	* +5V
03	GND
04	**Open Collector

\*+5V output in series with 100 ohms  
\*\*OC contacts at 350 ma max

### Related Products

## CTL-100 | Camera Tally Light

### Key Features

- Talent and Operator Tally light
- External tally trigger for monitors with supported tally input
- Talent tally on/off switch
- 1/4 20 mounting
- All metal construction
- Powers direct from main Interface no external power needed
- Extends greater than to 800 meters
- Main transmitter units TI-800 & TPI-400



External Tally	
01	LED
02	* +5V
03	GND
04	**Open Collector

\*+5V output in series with 100 ohms  
\*\*OC contacts at 350 ma max

# DTElabs

## DTL-100 Desktop Tally Light

## Specifications

DTL-100 Desktop Tally Light Module		
<b>Inputs</b>	<b>Specifications</b>	<b>Connectors</b>
Tally control Input from TI-800 or TPI-400	Tally control and Module power input	Neutrik CAT5e
<b>Outputs</b>	<b>Specifications</b>	<b>Connectors</b>
External tally interface	Pin 1 LED cathode; pin 2 LED anode, connects to +5V through 100 ohm series resistor; pin 3 GND; pin 4 OC contact at 350 ma max.	4-pin RJ11
<b>Indicators</b>	<b>Specifications</b>	<b>Connectors</b>
Operator Tally (red)	Bright LED indication	N/A
Indicator Range	Greater than 800 m (2,600 ft) over Cat5e cable	N/A
<b>Mechanical</b>	<b>Specifications</b>	
Tally Light Module	2"(50 mm)(H) x 4"(100 mm)(W) x 2"(50 mm)(D)	

Tally Interface Cables sold separately. Custom lengths available.  
Contact us for information and pricing.

Design and Specifications Subject to Change Without Notice.

NewTek Inc is not affiliated, associated, endorsed or sponsored by DTElabs, LLC.



# DTElabs

## CTL-100 Camera Tally Light

## Specifications

CTL-100 Camera Tally Light Module		
<b>Inputs</b>	<b>Specifications</b>	<b>Connectors</b>
Tally control Input from TI-800 or TPI-400	Tally control and Module power input	Neutrik CAT5e
<b>Outputs</b>	<b>Specifications</b>	<b>Connectors</b>
External tally interface	Pin 1 LED cathode; pin 2 LED anode, connects to +5V through 100 ohm series resistor; pin 3 GND; pin 4 OC contact at 350 ma max.	4-pin RJ11
<b>Indicators</b>	<b>Specifications</b>	<b>Connectors</b>
Talent Tally (red)	Bright LED indication with on/off switch control	N/A
Opertor Tally (red)	Bright LED indication	N/A
Indicator Range	Greater than 800 m (2,600 ft) over Cat5e cable	N/A
<b>Mechanical</b>	<b>Specifications</b>	
Tally Light Module	2"(50 mm)(H) x 4"(100 mm)(W) x 2"(50 mm)(D)	

Tally Interface Cables sold separately. Custom lengths available.  
Contact us for information and pricing.

Design and Specifications Subject to Change Without Notice.

NewTek Inc is not affiliated, associated, endorsed or sponsored by DTElabs, LLC.

